

62nd IETF Meeting - March 2005

IPPM Working Group

draft-stephan-ippm-multimetrics-00.txt

Emile Stephan – Lei Liang

Summary

- o Context
- o Motivations
- o Presentation of the IDs to merge
- o Method used to merge the 3 IDs
- o presentation of the resulting ID
- o Discussion

Context

- 54th IETF: draft-stephan-ippm-multicast-metrics-00.txt
Measuring the performance of multicast services
- 55th IETF: draft-stephan-ippm-spatial-metrics-00.txt
Decomposition & Aggregation of metrics results
- 61th IETF: draft-liang-multiparty-para-00.txt
Multiparty Communication parameters
- 62nd IETF:
 - Henk request:
 - opinion on Lei document
 - JP (PCE chair) request
 - Metrics to control path quality
- -> Merge 3 IDs in a potential WG document

Motivation for spatial metrics


- End-to-end measure decompositions:
 - clear and helpful information to identify tree branches or path segments with problems.
- PCE WG
 - end-to-end metrics definitions decomposition for controlling path quality.
- PSAMP WG
 - sampling techniques usable to measure one-way delay.
 - common metric to couple PSAMP packet observations and IPPM end-to-end measures.
- Traffic engineering and troubleshooting
 - require spatial views
 - one-way delay consumption
 - packet loss location identification.

Motivation for one-to-group metrics

- Simple one-way metric cannot describe a multi-connection situation. we need metrics to present the performance of a multiparty communication.
- One-to-group performance metrics are needed for several reasons:
 - For designing and engineering multicast trees and MPLS point-to-multipoint LSP;
 - For evaluating and controlling of the quality of the multicast services;
 - For presenting and evaluating the relative QoS requirements for the multiparty communications.


draft-stephan-ippm-spatial-metrics-00.txt

End-to-end metrics decomposition



Decompose the behavior of a packet send by H0 to Hn in the path H1,H2...


End-to-end metrics aggregation



Composition of e2e metrics from H0 to H1, H1 to H2...


draft-liang-multiparty-para-00.txt

One-to-group performance key indicator



- Statistics describing the performance from Src to the group of receivers.

Group-to-One performance key indicator




- Statistics describing the performance from the group of sources to Dst.

Method used to merge the 3 ID

- Methodology:
 - only metrics packets sends from one host
 - Low level metrics only: base for PKI computation
- Potential metrics
 - Multicast One-to-many metrics
 - End-to-end metrics decomposition
 - End-to-end metrics aggregation
 - One-to-Group performance key indicator
 - Group-to-One performance key indicator
- Selected metrics
 - End-to-end metrics decomposition & PKI discussion
 - One-to-Group metrics & PKI discussion

draft-stephan-ippm-multimetrics-00.txt


Spatial decomposition of end-to-end metrics



Type-P-Spatial-One-way-Delay-Stream <T*,dT1,dT2,...,dTn,dT*>

Metrics to analyse the performance of a path

One-to-group metrics



Type-P-one-to-group-One-way-Delay-Stream { dT1*, dT2*,...,dTn* }

Intermediary metrics to compute one-to-group PKI

*RFC2679 Singleton Type-P-One-way-Delay

Discussion